

### Features:

- Center amplifying gate
- Metal case with ceramic insulator
- Low on-state and switching losses

### Typical Applications

- AC controllers
- DC and AC motor control
- Controlled rectifiers

$I_{T(AV)}$       **1800 A**  
 $V_{DRM}/V_{RRM}$     **4500-5500V**  
 $I_{TSM}$             **22 kA**  
 $I^2t$                 **2420 10<sup>3</sup>A<sup>2</sup>S**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T <sub>J</sub> (°C)	VALUE			UNIT
					Min	Type	Max	
I <sub>T(AV)</sub>	Mean on-state current	180° half sine wave 50Hz Double side cooled,	T <sub>C</sub> =70°C	125			1800	A
V <sub>DRM</sub> V <sub>RRM</sub>	Repetitive peak off-state voltage Repetitive peak reverse voltage	tp=10ms		125	4500		5500	V
I <sub>DRM</sub> I <sub>RRM</sub>	Repetitive peak current	at V <sub>DRM</sub> at V <sub>RRM</sub>		125			350	mA
I <sub>TSM</sub>	Surge on-state current	10ms half sine wave		125			22	kA
I <sup>2</sup> t	I <sup>2</sup> t for fusing coordination	V <sub>R</sub> =0.6V <sub>RRM</sub>					2420	A <sup>2</sup> s*10 <sup>3</sup>
V <sub>TO</sub>	Threshold voltage			125			1.01	V
r <sub>T</sub>	On-state slope resistance						0.36	mΩ
V <sub>TM</sub>	Peak on-state voltage	I <sub>TM</sub> =3000A, F=40kN		25			2.20	V
dv/dt	Critical rate of rise of off-state voltage	V <sub>DM</sub> =0.67V <sub>DRM</sub>		125			2000	V/μs
di/dt	Critical rate of rise of on-state current	V <sub>DM</sub> = 67%V <sub>DRM</sub> to 3000A, Gate pulse tr ≤0.5μs IGM= 1.5A		125			200	A/μs
Q <sub>rr</sub>	Recovery charge	I <sub>TM</sub> =2000A, tp=2000μs, di/dt=-5A/μs, V <sub>R</sub> =50V		125		3500		μC
I <sub>GT</sub>	Gate trigger current	VA=12V, IA=1A		25	40		300	mA
V <sub>GT</sub>	Gate trigger voltage				0.8		3.0	V
I <sub>H</sub>	Holding current				25		200	mA
V <sub>GD</sub>	Non-trigger gate voltage	V <sub>DM</sub> =67%V <sub>DRM</sub>		125	0.3			V
R <sub>th(j-c)</sub>	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 40.0kN					0.011	°C /W
R <sub>th(c-h)</sub>	Thermal resistance case to heatsink						0.003	°C /W
F <sub>m</sub>	Mounting force				35	40	47	kN
T <sub>stg</sub>	Stored temperature				-40		140	°C
W <sub>i</sub>	Weight					1140		g
Outline	KT60dT							




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig.7




Fig.8




Fig.9




Fig.10

Outline:

